

OB1313



Use With: BT287 Series, BT351, BT387 Series, BT388 Series, BT389 Series, B7011, BT8307-MPG, BT8308-MPG-KIT, BT8309-MPG, BT8310-MPG, BT8368, BT8421-MPG, BT8422-MPG, BT8423, BT8424-MPG

Notes: For use on the suction side.

Contains: 3 PSID By-Pass Threaded Stud 1 1/2-16 Threaded Stud 1 1/4-11 BSP

O.D.: 5 1/2 (139.7)
Inlet: 1 1/4-11 1/2 NPT
Outlet: 1 1/4-11 1/2 NPT
Height: 5 5/16 (134.9)

OB1314



Replaces: Donaldson P167849
Use With: BT287 Series, BT351, BT387 Series, BT388 Series, BT389 Series, B7011, BT8307-MPG, BT8308-MPG-KIT, BT8309-MPG, BT8310-MPG, BT8368, BT8421-MPG, BT8422-MPG, BT8423, BT8424-MPG

Notes: For use on the return side.

Contains: 25 PSID By-Pass Threaded Stud 1 1/2-16 Threaded Stud 1 1/4-11 BSP

O.D.: 5 1/2 (139.7)
Inlet: 1 1/4 In. NPT
Outlet: 1 1/4 In. NPT
Height: 5 5/16 (134.9)

OB1315



Use With: BT287 Series, BT351, BT387 Series, BT388 Series, BT389 Series, B7011, BT8307-MPG, BT8308-MPG-KIT, BT8309-MPG, BT8310-MPG, BT8368, BT8421-MPG, BT8422-MPG, BT8423, BT8424-MPG

Notes: For use on the suction side.

Contains: 5 PSID By-Pass Threaded Stud 1 1/2-16 Threaded Stud 1 1/4-11 BSP

O.D.: 5 13/32 (137.3)
Inlet: 1 5/8-12 In. SAE
Outlet: 1 5/8-12 In. SAE
Height: 5 5/16 (134.9)

OB1316



Use With: BT287 Series, BT351, BT387 Series, BT388 Series, BT389 Series, B7011, BT8307-MPG, BT8308-MPG-KIT, BT8309-MPG, BT8310-MPG, BT8368, BT8421-MPG, BT8422-MPG, BT8423, BT8424-MPG

Notes: For use on the return side.

Contains: 25 PSID By-Pass Threaded Stud 1 1/2-16 Threaded Stud 1 1/4-11 BSP

O.D.: 5 13/32 (137.3)
Inlet: 1 5/8-12 In. SAE
Outlet: 1 5/8-12 In. SAE
Height: 5 5/16 (134.9)

OB1317



Replaces: Donaldson P171207
Use With: BT839 Series, BT8420, BT8428-MPG, BT8443

Notes: For use on the suction side.

Contains: 5 PSID By-Pass Threaded Stud 1-12 [2] 1/8 In. NPT Indicator Ports

O.D.: 3 3/4 (95.3)
Inlet: 3/4-14 NPT
Outlet: 3/4-14 NPT
Height: 3 (76.2)

OB1318



Replaces: Donaldson P167848
Use With: BT839 Series, BT8420, BT8428-MPG, BT8443

Notes: For use on the return side.

Contains: 25 PSID By-Pass Threaded Stud 1-12 [2] 1/8 In. NPT Indicator Ports

O.D.: 3 (76.2)
Inlet: 3/4 In. NPT
Outlet: 3/4 In. NPT
Height: 3 3/4 (95.3)

OB1319



Use With: BT839 Series, BT8420, BT8428-MPG, BT8443

Notes: For use on the suction side.

Contains: 5 PSID By-Pass Threaded Stud 1-12 [2] 1/8 In. NPT Indicator Ports

O.D.: 3 3/4 (95.3)
Inlet: 1 1/16-12 ORB
Outlet: 1 1/16-12 ORB
Height: 3 (76.2)

OB1320



Use With: BT839 Series, BT8420, BT8428-MPG, BT8443

Notes: For use on the return side.

Contains: 25 PSID By-Pass Threaded Stud 1-12 [2] 1/8 In. NPT Indicator Ports

O.D.: 3 3/4 (95.3)
Inlet: 1 1/16-12 ORB
Outlet: 1 1/16-12 ORB
Height: 3 (76.2)

OB8711



Replaces: Donaldson P169317
Use With: 4 Inch O.D. PureForce Filters

Contains: 25 PSID By-Pass Valve Threaded Stud: 1 3/8-12 [2] Indicator Ports with Plugs

O.D.: 3 31/32 (100.8)
Inlet: 3/4 In. NPT
Outlet: 3/4 In. NPT
Height: 4 (101.6)

OB8712



Replaces: Donaldson P169310
Use With: 4 Inch O.D. PureForce Filters

Contains: 25 PSID By-Pass Valve Threaded Stud: 1 3/8-12 [2] Indicator Ports Visual Indicator Mounted on Left Side

O.D.: 3 31/32 (100.8)
Inlet: 3/4 In. NPT
Outlet: 3/4 In. NPT
Height: 4 (101.6)

OB8720



Replaces: Donaldson P165434
Use With: 4 Inch O.D. PureForce Filters

Contains: Threaded Stud: 1 3/8-12
Note: Not intended for indicator use.

O.D.: 3 31/32 (100.8)
Inlet: 3/4 In. SAE O-Ring (1 1/16-12 Thread)
Outlet: 3/4 In. SAE O-Ring (1 1/16-12 Thread)
Height: 4 (101.6)

OB8721



Replaces: Donaldson P167473
Use With: 4 Inch O.D. PureForce Filters

Contains: 25 PSID By-Pass Valve Threaded Stud: 1 3/8-12 [2] Indicator Ports with Plugs

O.D.: 3 31/32 (100.8)
Inlet: 3/4 In. SAE O-Ring (1 1/16-12 Thread)
Outlet: 3/4 In. SAE O-Ring (1 1/16-12 Thread)
Height: 4 (101.6)

OB8722



Replaces: Donaldson P166387
Use With: 4 Inch O.D. PureForce Filters

Contains: 25 PSID By-Pass Valve Threaded Stud: 1 3/8-12 [2] Indicator Ports Visual Indicator Mounted on Left Side

O.D.: 3 31/32 (100.8)
Inlet: 3/4 In. SAE O-Ring (1 1/16-12 Thread)
Outlet: 3/4 In. SAE O-Ring (1 1/16-12 Thread)
Height: 4 (101.6)

OB8724



Use With: 4 Inch O.D. PureForce Filters

Contains: 50 PSID By-Pass Valve Threaded Stud: 1 3/8-12 [2] Indicator Ports with Plugs

O.D.: 3 3/8 (85.7)
Inlet: 3/4 In. SAE O-Ring (1 1/16-12 Thread)
Outlet: 3/4 In. SAE O-Ring (1 1/16-12 Thread)
Height: 4 (101.6)

OB8726



Use With: 4 Inch O.D. PureForce Filters

Notes: Normally Open
Contains: 50 PSID By-Pass Valve Threaded Stud: 1 3/8-12 [2] Indicator Ports Single Post Indicator Mounted on Left Side

O.D.: 3 31/32 (100.8)
Inlet: 3/4 In. SAE O-Ring (1 1/16-12 Thread)
Outlet: 3/4 In. SAE O-Ring (1 1/16-12 Thread)
Height: 4 (101.6)

OB8731



Replaces: Donaldson P169309
Use With: 4 Inch O.D. PureForce Filters

Contains: 25 PSID By-Pass Valve Threaded Stud: 1 3/8-12 [2] Indicator Ports with Plugs

O.D.: 3 31/32 (100.8)
Inlet: 1 In. NPT
Outlet: 1 In. NPT
Height: 4 (101.6)

OB8732

Replaces: Donaldson P166416
Use With: 4 Inch O.D. PureForce Filters
Contains: 25 PSID By-Pass Valve
 Threaded Stud: 1 3/8-12
 [2] Indicator Ports
 Visual Indicator Mounted on Left Side
O.D.: 3 31/32 (100.8)
Inlet: 1 In. NPT
Outlet: 1 In. NPT
Height: 4 (101.6)

OB8740

Use With: 4 Inch O.D. PureForce Filters
Contains: Threaded Stud: 1 3/8-12
Note: Not intended for indicator use.
O.D.: 3 31/32 (100.8)
Inlet: 1 In. SAE O-Ring (1 5/16-12 Thread)
Outlet: 1 In. SAE O-Ring (1 5/16-12 Thread)
Height: 4 (101.6)

OB8741

Replaces: Donaldson P163681
Use With: 4 Inch O.D. PureForce Filters
Contains: 25 PSID By-Pass Valve
 Threaded Stud: 1 3/8-12
 [2] Indicator Ports with Plugs
O.D.: 3 31/32 (100.8)
Inlet: 1 In. SAE O-Ring (1 5/16-12 Thread)
Outlet: 1 In. SAE O-Ring (1 5/16-12 Thread)
Height: 4 (101.6)

OB8742

Replaces: Donaldson P166417
Use With: 4 Inch O.D. PureForce Filters
Contains: 25 PSID By-Pass Valve
 Threaded Stud: 1 3/8-12
 [2] Indicator Ports
 Visual Indicator Mounted on Left Side
O.D.: 3 31/32 (100.8)
Inlet: 1 In. SAE O-Ring (1 5/16-12 Thread)
Outlet: 1 In. SAE O-Ring (1 5/16-12 Thread)
Height: 4 (101.6)

OB8743

Replaces: Donaldson P165537
Use With: 4 Inch O.D. PureForce Filters
Notes: Normally Open
Contains: 25 PSID By-Pass Valve
 Threaded Stud 1 3/8-12
 [2] Indicator Ports
 Single Post Indicator Mounted on Left Side
O.D.: 3 31/32 (100.8)
Inlet: 1 In. SAE O-Ring (1 5/16-12 Thread)
Outlet: 1 In. SAE O-Ring (1 5/16-12 Thread)
Height: 4 (101.6)

OB8744

Replaces: Donaldson P167201
Use With: 4 Inch O.D. PureForce Filters
Contains: 50 PSID By-Pass Valve
 Threaded Stud: 1 3/8-12
 [2] Indicator Ports with Plugs
O.D.: 3 3/8 (85.7)
Inlet: 1 In. SAE O-Ring (1 5/16-12 Thread)
Outlet: 1 In. SAE O-Ring (1 5/16-12 Thread)
Height: 4 (101.6)

OB8745

Use With: 4 Inch O.D. PureForce Filters
Contains: 50 PSID By-Pass Valve
 Threaded Stud: 1 3/8-12
 [2] Indicator Ports
 Visual Indicator Mounted on Left Side
O.D.: 3 31/32 (100.8)
Inlet: 1 In. SAE O-Ring (1 5/16-12 Thread)
Outlet: 1 In. SAE O-Ring (1 5/16-12 Thread)
Height: 4 (101.6)

OB8746

Replaces: Donaldson P166862
Use With: 4 Inch O.D. PureForce Filters
Notes: Normally Open
Contains: 50 PSID By-Pass Valve
 Threaded Stud: 1 3/8-12
 [2] Indicator Ports
 Single Post Indicator Mounted on Left Side
O.D.: 3 31/32 (100.8)
Inlet: 1 In. SAE O-Ring (1 5/16-12 Thread)
Outlet: 1 In. SAE O-Ring (1 5/16-12 Thread)
Height: 4 (101.6)

OB8771

Use With: 5 Inch O.D. PureForce Filters
Contains: 25 PSID By-Pass Valve
 Threaded Stud: 1 3/4-12
 [2] Indicator Ports with Plugs
O.D.: 4 1/2 (114.3)
Inlet: 1 1/4 In. NPT
Outlet: 1 1/4 In. NPT
Height: 5 (127.0)

OB8772

Use With: 5 Inch O.D. PureForce Filters
Contains: 25 PSID By-Pass Valve
 Threaded Stud: 1 3/4-12
 [2] Indicator Ports
 Visual Indicator Mounted on Left Side
O.D.: 4 1/2 (114.3)
Inlet: 1 1/4 In. NPT
Outlet: 1 1/4 In. NPT
Height: 5 (127.0)

OB8773

Replaces: Donaldson P167621
Use With: 5 Inch O.D. PureForce Filters
Notes: Normally Open
Contains: 25 PSID By-Pass Valve
 Threaded Stud: 1 3/4-12
 [2] Indicator Ports
 Single Post Indicator Mounted on Left Side
O.D.: 4 1/2 (114.3)
Inlet: 1 1/4 In. NPT
Outlet: 1 1/4 In. NPT
Height: 5 (127.0)

OB8781

Replaces: Donaldson P167619
Use With: 5 Inch O.D. PureForce Filters
Contains: 25 PSID By-Pass Valve
 Threaded Stud: 1 3/4-12
 [2] Indicator Ports with Plugs
O.D.: 4 1/2 (114.3)
Inlet: 1 1/4 SAE O-Ring (1 5/8-12 Thread)
Outlet: 1 1/4 SAE O-Ring (1 5/8-12 Thread)
Height: 5 (127.0)

OB8783

Use With: 5 Inch O.D. PureForce Filters
Contains: 25 PSID By-Pass Valve
 Threaded Stud: 1 3/4-12
 [2] Indicator Ports
 Visual Indicator Mounted on Left Side
O.D.: 4 1/2 (114.3)
Inlet: 1 1/4 SAE O-Ring (1 5/8-12 Thread)
Outlet: 1 1/4 SAE O-Ring (1 5/8-12 Thread)
Height: 5 (127.0)

BALDWIN	DONALDSON	FLEETGUARD	FRAM	LUBER-FINER	WIX
OB1313	—	—	—	—	—
OB1314	P167849	—	—	—	24759
OB1315	—	—	—	—	—
OB1316	—	—	—	—	—
OB1317	P171207	—	—	—	—
OB1318	P167848	—	—	—	—
OB1319	—	—	—	—	—
OB1320	—	—	—	—	—
OB8711	P169317	—	—	—	—
OB8712	P169310	—	—	—	—
OB8720	P165434	—	—	—	—
OB8721	P167473	—	—	—	—
OB8722	P166387	—	—	—	—
OB8724	—	—	—	—	—
OB8726	—	—	—	—	—
OB8731	P169309	—	—	—	—
OB8732	P166416	—	—	—	—
OB8740	—	—	—	—	—
OB8741	P163681	—	—	—	—
OB8742	P166417	—	—	—	—
OB8743	P165537	—	—	—	—
OB8744	P167201	—	—	—	—
OB8745	—	—	—	—	—
OB8746	P166862	—	—	—	—
OB8771	—	—	—	—	—
OB8772	—	—	—	—	—
OB8773	—	—	—	—	—
OB8773	P167621	—	—	—	—
OB8781	P167619	—	—	—	—
OB8783	—	—	—	—	—